

Container	Description	Configuration Temp (°C/°F)	Performance in hours at 30°C/86°F	External Dims (mm)	Payload Dims (mm)	Payload Volume (litres)	System Weight (kg)	Volumetric (kg) (6000cc)
 KT400D	Sub-pallet, ultra-cold payload for narrow-bodied aircraft and light goods vehicles	-80 to -60 / -112 to -76	120+	(W L H) 1200 x 800 x 1050	(W L H) 947 x 537 x 585*	297	70*	168
 KT400F KT400R-S KT400R-H KT400T	Sub-pallet payload for narrow-bodied aircraft and light goods vehicles. KT400R-H specially designed for extreme conditions	-25 to -15 / -13 to +5 +2 to +8 / +35 to +46 +2 to +8 / +35 to +46 +15 to +25 / +59 to +77	120+ 120+ 120+ 120+	1200 x 800 x 1050 1200 x 800 x 1050 1200 x 800 x 1050 1200 x 800 x 1050	900 x 500 x 585 900 x 500 x 585 900 x 500 x 485 900 x 500 x 585	263 263 218 263	220 188 216 248	168 168 168 168
 KTM21F KTM21R KTM21T	"Low" Euro pallet payload. for narrow-bodied aircraft and light goods vehicles	-25 to -15 / -13 to +5 +2 to +8 / +35 to +46 +15 to +25 / +59 to +77	120+ 120+ 120+	1550 x 1130 x 930 1550 x 1130 x 930 1550 x 1130 x 930	1250 x 820 x 550 1250 x 820 x 550 1250 x 820 x 550	564 564 564	305 269 322	271 271 271
 KTM31F KTM31R KTM31T	"Low" US pallet payload. for narrow-bodied aircraft and light goods vehicles	-25 to -15 / -13 to +5 +2 to +8 / +35 to +46 +15 to +25 / +59 to +77	120+ 120+ 120+	1150 x 1540 x 930 1150 x 1540 x 930 1150 x 1540 x 930	1250 x 1230 x 550 1250 x 1230 x 550 1250 x 1230 x 550	846 846 846	393 344 415	370 370 370
 KTM22F KTM22R KTM22T	Single Euro pallet payload for wide-bodied aircraft and light goods vehicles	-25 to -15 / -13 to +5 +2 to +8 / +35 to +46 +15 to +25 / +59 to +77	120+ 120+ 120+	1150 x 1130 x 1580 1150 x 1130 x 1580 1150 x 1130 x 1580	1250 x 820 x 1200 1250 x 820 x 1200 1250 x 820 x 1200	1230 1230 1230	457 400 483	461 461 461
 KTM32F KTM32R KTM32T	Single US pallet payload for wide-bodied aircraft and pallet vehicles	-25 to -15 / -13 to +5 +2 to +8 / +35 to +46 +15 to +25 / +59 to +77	120+ 120+ 120+	1550 x 1540 x1580 1550 x 1540 x1580 1550 x 1540 x1580	1250 x 1230 x 1200 1250 x 1230 x 1200 1250 x 1230 x 1200	1845 1845 1845	576 503 609	629 629 629
 KTM42F KTM42R KTM42T	Double Euro pallet payload for wide-bodied aircraft and pallet vehicles	-25 to -15 / -13 to +5 +2 to +8 / +35 to +46 +15 to +25 / +59 to +77	120+ 120+ 120+	1550 x 1950 x 1580 1550 x 1950 x 1580 1550 x 1950 x 1580	1250 x 1640 x 1200 1250 x 1640 x 1200 1250 x 1640 x 1200	2460 2460 2460	710 621 751	796 796 796
 KTM42D	Ultra Cold, Double Euro pallet payload for wide-bodied aircraft and pallet vehicles	-80 to -60 / -112 to -76	120+	1550 x 1950 x 1580	1250 x 1640 x 1050	2153	617	796
 KTM52F KTM52R KTM52T	Double US pallet payload for wide-bodied aircraft and pallet vehicles	-25 to -15 / -13 to +5 +2 to +8 / +35 to +46 +15 to +25 / +59 to +77	120+ 120+ 120+	1550 x 2360 x 1580 1550 x 2360 x 1580 1550 x 2360 x 1580	1250 x 2050 x 1200 1250 x 2050 x 1200 1250 x 2050 x 1200	3075 3075 3075	840 734 888	963 963 963
 KTEvolution26 D KTEvolution26 F KTEvolution26 R KTEvolution26 T	Hand-held container is a manually handleable by two persons, weatherproof, and washable supply chain solution.	<-60 / <-76 -25 to -15 / -13 to +5 +2 to +8 / +35 to +46 +15 to +25 / +59 to +77	120+	403 x 443 x 545 403 x 443 x 545 403 x 443 x 545 403 x 443 x 545	260 x 300 x 340 260 x 300 x 340 260 x 300 x 340 260 x 300 x 340	26.5	21.5 26 21.5 29	16.2
 KTEvolution57 D KTEvolution57 F KTEvolution57 R KTEvolution57 T	Hand-held container is a manually handleable by two persons, weatherproof, and washable supply chain solution.	<-60 / <-76 -25 to -15 / -13 to +5 +2 to +8 / +35 to +46 +15 to +25 / +59 to +77	120+	443 x 703x 545 443 x 703x 545 443 x 703x 545 443 x 703x 545	300 x 560 x 340 300 x 560 x 340 300 x 560 x 340 300 x 560 x 340	57.1	31 41 33 46	28.3